



How to change tailgate  
struts on **Peugeot 107**  
**PM PN** – replacement  
guide

## VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:  
PEUGEOT 107 Hatchback (PM, PN) 1.4 HDi

The steps may slightly vary depending on the car design.

REPLACEMENT: TAILGATE STRUTS – PEUGEOT 107 PM  
PN. TOOLS YOU NEED:



- Phillips screwdriver
- Flat Screwdriver
- Hydraulic transmission jack

**BUY TOOLS**


Replacement: tailgate struts – Peugeot 107 PM PN. AUTODOC recommends:

- Right and left gas struts of the boot lid should be replaced simultaneously.
- The replacement procedure is identical for the right and left gas struts of the boot lid.
- All work should be done with the engine stopped.

## REPLACEMENT: TAILGATE STRUTS – PEUGEOT 107 PM PN. USE THE FOLLOWING PROCEDURE:


1

Open the boot lid.



2


Support the boot lid. Use a hydraulic transmission jack.




**3** Release the circlip connecting the gas strut to the boot lid. Use a flat screwdriver.



**4** Unscrew the fastener of the boot side lining. Use a Phillips screwdriver.



**5** Release the circlip connecting the gas strut to the car body. Use a flat screwdriver.



**Replacement: tailgate struts – Peugeot 107 PM PN. Professionals recommend:**

- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.

**6** Remove the boot lid gas strut.

**7** Install the new boot lid gas strut.

Replacement: tailgate struts – Peugeot 107 PM PN. Tip from AUTODOC:

- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.


**8** Snap on the circlip connecting the gas strut to the car body.




**9** Snap on the circlip connecting the gas strut to the boot lid.



**10** Screw in the fastener of the boot side lining. Use a Phillips screwdriver.



**11** Remove the hydraulic transmission jack.



Replacement: tailgate struts – Peugeot 107 PM PN. AUTODOC experts recommend:

- Lower the hydraulic transmission jack smoothly, without jerks, to avoid damaging assemblies and mechanisms.

12

Check the working condition of the boot lid gas springs after they are installed.

13

Close the lid of the luggage compartment.



**WELL DONE!** 

[VIEW MORE TUTORIALS](#)

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  **Google Play**

 **Download on the App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR PEUGEOT**

**TAILGATE STRUTS: A WIDE SELECTION**



**CHOOSE CAR PARTS FOR PEUGEOT 107 PM PN**

**TAILGATE STRUTS FOR PEUGEOT: BUY NOW**

**TAILGATE STRUTS FOR PEUGEOT 107 PM PN: THE BEST  
DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.