




How to change track rod
end on **Peugeot 206 CC**
2D – replacement guide

VIDEO TUTORIAL



ⓘ Important!

This replacement procedure can be used for:

PEUGEOT 305 II Saloon 1.5, PEUGEOT 305 II Saloon 1.9 D, PEUGEOT 305 II Estate 1.3, PEUGEOT 305 I Estate 1.3, PEUGEOT 305 II Estate 1.5, PEUGEOT 305 I Estate 1.5, PEUGEOT 605 Saloon 2.1 Turbo diesel, PEUGEOT 605 Saloon 2.0, PEUGEOT 605 Saloon 2.0 Turbo, PEUGEOT 605 Saloon 3.0, PEUGEOT 605 Saloon 3.0 SV 24, PEUGEOT 106 I Hatchback 1.4 D, PEUGEOT 106 I Hatchback 1.0, PEUGEOT 106 I Hatchback 1.1, PEUGEOT 106 I Hatchback 1.3, (+ 105)

The steps may slightly vary depending on the car design.

REPLACEMENT: TRACK ROD END – PEUGEOT 206 CC 2D. TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Combination spanner #20
- Combination spanner #22
- Drive socket # 17
- Wheel impact socket #19
- Ratchet wrench
- Torque wrench
- Vernier caliper
- Tap wrench
- Hammer
- Pin punch
- Wheel chock

[BUY TOOLS](#)

Replacement: track rod end – Peugeot 206 CC 2D. AUTODOC recommends:

- Replace tie rod ends in pairs.
- The replacement procedure is identical for the right and left tie rod ends.
- Please note: all work on the car – Peugeot 206 CC 2D – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #19.




3

Raise the front of the car and secure on supports.



4

Unscrew the wheel bolts.




Replacement: track rod end – Peugeot 206 CC 2D. Tip:

- To avoid injury, hold up the wheel when unscrewing the bolts.


5

Remove the wheel.




6

When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.




7

Loosen the lock nut securing the tie rod end to the tie rod. Use a combination spanner #22.



8

Clean the fastener connecting the tie rod end to the steering knuckle. Use a wire brush. Use WD-40 spray.



9

Unscrew the end fastening nut to the steering knuckle. Use a drive socket #17. Use a tap wrench.




10

Disconnect the tie rod end from the steering knuckle. Use a pin punch. Use a hammer.




11 Screw the end out of the tie rod.



12 Clean the mounting seats of the tie rod end. Use a wire brush. Use WD-40 spray.




13 Screw on a new tie rod end.




Replacement: track rod end – Peugeot 206 CC 2D. AUTODOC experts recommend:

- While installing the steering rod end remember to make the same number of turns or to leave the same length of thread showing as per your measurements.

- 14** Connect the tie rod end to the steering knuckle.




- 15** When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.




- 16** Treat the threaded part of the tie rod. Use copper grease.

- 17** Screw on the fastening nut that connects the tie rod end to the steering knuckle. Use a drive socket #17. Use a ratchet wrench.




- 18** Tighten the tie rod end locknut. Use a combination spanner #20. Use a combination spanner #22. Use a torque wrench. Tighten it to 55 nm torque.

- 19** Tighten the fastening nut connecting the tie rod end to the steering knuckle. Use a drive socket #17. Use a torque wrench. Tighten it to 35 nm torque.



20

Treat the fastener connecting the tie rod end to the steering knuckle. Use copper grease.




21

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



22

Clean the brake disk surface. Use a brake cleaner.




AUTODOC recommends:

- Replacement: track rod end – Peugeot 206 CC 2D. After applying the spray, wait a few minutes.

23

Install the wheel.



Replacement: track rod end – Peugeot 206 CC 2D. Tip from AUTODOC experts:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.


24

Screw in the wheel bolts. Use wheel impact socket #19.



25

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 100 nm torque.




Replacement: track rod end – Peugeot 206 CC 2D. Tip:

- Check and adjust wheel alignment if necessary.

26

Remove the jacks and chocks.

**WELL DONE!** **VIEW MORE TUTORIALS**

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR PEUGEOT

TRACK ROD END: A WIDE SELECTION

CHOOSE CAR PARTS FOR PEUGEOT 206 CC 2D

TRACK ROD END FOR PEUGEOT: BUY NOW

**TRACK ROD END FOR PEUGEOT 206 CC 2D: THE BEST
DEALS & OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.