



How to change front anti  
roll bar links on  
**PEUGEOT 5008 I (0U\_,  
0E\_)** – replacement guide

### SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

#### **i Important!**

This replacement procedure can be used for:

PEUGEOT 5008 I (0U\_, 0E\_) 1.6 HDi, PEUGEOT 5008 I (0U\_, 0E\_) 2.0 HDi 136 / BlueHDi 136, PEUGEOT 5008 I (0U\_, 0E\_) 1.6 16V, PEUGEOT 5008 I (0U\_, 0E\_) 2.0 HDi 150 / BlueHDi 150, PEUGEOT 5008 I (0U\_, 0E\_) 2.0 HDi, PEUGEOT 5008 I (0U\_, 0E\_) 1.6 THP 150, PEUGEOT 5008 I (0U\_, 0E\_) 1.6 THP 163, PEUGEOT 5008 I (0U\_, 0E\_) 1.6 BlueHDi 120, PEUGEOT 5008 I (0U\_, 0E\_) 1.2, PEUGEOT 5008 I (0U\_, 0E\_) 1.6 THP 165

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: PEUGEOT 307 SW (3H) 2.0 HDi 135

REPLACEMENT: ANTI ROLL BAR LINKS – PEUGEOT 5008 I (0U\_, 0E\_). TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Combination spanner #16
- Drive socket # 15
- Drive socket # 17
- Wheel impact socket #17
- Ratchet wrench
- Wheel chock

**Buy tools**

Replacement: anti roll bar links – PEUGEOT 5008 I (0U\_, 0E\_). AUTODOC experts recommend:

- Replace the stabiliser links on PEUGEOT 5008 I (0U\_, 0E\_) in pairs.
- The replacement procedure is identical for both stabiliser links on the same axle.
- All work should be done with the engine stopped.

## REPLACEMENT: ANTI ROLL BAR LINKS – PEUGEOT 5008 I (0U\_, 0E\_). RECOMMENDED SEQUENCE OF STEPS:


**1** Secure the wheels with chocks.

**2** Loosen the wheel mounting bolts. Use wheel impact socket #17.



**3** Raise the front of the car and secure on supports.

**4** Unscrew the wheel bolts.



Replacement: anti roll bar links – PEUGEOT 5008 I (0U\_, 0E\_). AUTODOC recommends:

- To avoid injury, hold up the wheel when unscrewing the bolts.

5

Remove the wheel.



6

Remove the ABS wiring harness bracket.



7

Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.



- 8 Unscrew the fastener connecting the stabilizer link to the shock strut. Use a drive socket #15. Use a ratchet wrench.



- 9 Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.



- 10 Unscrew the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #16. Use a drive socket #15. Use a ratchet wrench.



- 11 Remove the stabilizer rod.



Replacement: anti roll bar links – PEUGEOT 5008 I (0U\_, 0E\_). Tip from AUTODOC experts:

- Examine stabiliser bushes. Replace them if needed.

12

Clean the mounting seats of the stabiliser link. Use a wire brush. Use WD-40 spray.



13

Install a new rod, tighten the fasteners.



14

Tighten the fastener connecting the stabilizer link to the stabilizer bar. Use a drive socket #17. Use a torque wrench. Tighten it to 36 Nm torque.



- 15** Tighten the fastener connecting the stabilizer link to the shock strut. Use a drive socket #17. Use a torque wrench. Tighten it to 36 Nm torque.



- 16** Treat all joints of the stabiliser link. Use copper grease.



- 17** Install the ABS wiring harness bracket.



- 18** Treat the surface where the brake disc contacts the wheel rim. Use copper grease.





19

Clean the brake disk surface. Use a brake cleaner.



**AUTODOC recommends:**

- Replacement: anti roll bar links – PEUGEOT 5008 I (0U\_, 0E\_). After applying the spray, wait a few minutes.

20

Install the wheel.



**Replacement: anti roll bar links – PEUGEOT 5008 I (0U\_, 0E\_). Tip from AUTODOC:**

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

21

Screw in the wheel bolts. Use wheel impact socket #17.



**22**

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 100 nm torque.

**23**

Remove the jacks and chocks.



**WELL DONE!** 

**VIEW MORE TUTORIALS**

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**ANTI ROLL BAR LINKS: A WIDE SELECTION**

## **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.