



How to change
serpentine belt on **VW**
Polo 5 – replacement
guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:

VW Golf VI Convertible (517) 1.4 TSI, VW Jetta Mk6 (162, 163, AV3, AV2) 1.4 TSI, VW Polo V Saloon (602, 604, 612, 614) 1.6, VW Polo IV Hatchback (9N) 1.4 FSI, VW Touran I (1T1, 1T2) 1.6 FSI, VW Golf V Hatchback (1K1) 1.6 FSI, VW Golf V Hatchback (1K1) 1.4 FSI, VW Golf Plus / Crossgolf (5M1, 521) 1.6 FSI, VW Jetta Mk5 (1K) 1.6 FSI, VW Eos (1F7, 1F8) 1.6 FSI, VW Polo IV Hatchback (9N) 1.6 16V, VW Golf Plus / Crossgolf (5M1, 521) 1.4 FSI, VW Golf V Hatchback (1K1) 1.4 TSI, VW Golf V Variant (1K5) 1.4 TSI, VW Golf Plus / Crossgolf (5M1, 521) 1.4 TSI, (+ 12)

The steps may slightly vary depending on the car design.

REPLACEMENT: SERPENTINE BELT – VW POLO 5. TOOLS YOU NEED:



- Combination spanner #16

- Fender cover

[BUY TOOLS](#)

Replacement: serpentine belt – VW Polo 5. Tip from AUTODOC experts:

- All work should be done with the engine stopped.

REPLACEMENT: SERPENTINE BELT – VW POLO 5. TAKE THE FOLLOWING STEPS:


1

Open the hood.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Pull aside the V-ribbed belt tensioner pulley. Use a combination spanner #16.



4

Remove the V-ribbed belt.



5

Return the tensioner pulley to its initial position.

Replacement: serpentine belt – VW Polo 5. AUTODOC recommends:

- Check the condition of the tensioner pulley and idler pulley. Replace them if necessary.

6


Install the V-ribbed belt.




Replacement: serpentine belt – VW Polo 5. Tip:

- Make sure that the V-ribbed belt fits all pulleys snugly.

7 Pull aside the V-ribbed belt tensioner pulley. Use a combination spanner #16.



8 Place the V-ribbed belt on the tensioner pulley.



9 Return the tensioner pulley to its initial position. Use a combination spanner #16.



10 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

11 Shut off the engine.

12 Remove the fender protection cover.



13

Close the hood.



WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING

AUTODOC+

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VW

SERPENTINE BELT: A WIDE SELECTION

CHOOSE CAR PARTS FOR VW POLO 5

SERPENTINE BELT FOR VW: BUY NOW

SERPENTINE BELT FOR VW POLO 5: THE BEST DEALS & OFFERS

ⓘ DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.