How to change front brake discs on **Toyota RAV4 II** – replacement guide



VIDEO TUTORIAL




(i) Important!

This replacement procedure can be used for: TOYOTA RAV 4 II (CLA2_, XA2_, ZCA2_, ACA2_) 1.8 (ZCA25_, ZCA26_), TOYOTA RAV 4 II (CLA2_, XA2_, ZCA2_, ACA2_) 2.0 D 4WD (CLA20_, CLA21_), TOYOTA RAV 4 II (CLA2_, XA2_, ZCA2_, ACA2_) 2.4 4WD, TOYOTA RAV 4 II (CLA2_, XA2_, ZCA2_, ACA2_) 2.0

The steps may slightly vary depending on the car design.



REPLACEMENT: BRAKE DISCS – TOYOTA RAV4 II. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- All-purpose cleaning spray
- Brake cleaner
- Anti-squeal paste
- Ceramic grease
- Torque wrench

- Combination spanner #14
- Combination spanner #17
- Drive socket # 14
- Wheel impact socket #19
- Ratchet wrench
- Brake caliper wind back tool
- Crow bar
- Wheel chock

BUY TOOLS



AUTODOC recommends:

- Replace the brake disks on the car Toyota RAV4 II in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- Please note: all work on the car Toyota RAV4 II should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the bonnet. Unscrew the brake fluid reservoir cap.



2

Secure the wheels with chocks.



Loosen the wheel mounting bolts. Use wheel impact socket #19.







Raise the car.



Replacement: brake discs – Toyota RAV4 II. Tip from AUTODOC experts:

- If you are using a jack, make sure it rests on a flat surface without any unevenness.
- Be sure to additionally secure the car with jack stands.

Unscrew the wheel bolts.



AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts. Toyota RAV4 II





Remove the wheel.



7

Spread the brake pads. Use a crowbar.



8

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



9

Unscrew the brake caliper fasteners. Use a combination spanner #14.



10

Remove the fastening bolts.







Remove the brake caliper.



Replacement: brake discs – Toyota RAV4 II. AUTODOC recommends:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.

12

Remove the brake pads.



13

Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.





Unscrew the brake caliper bracket fasteners. Use a drive socket #17. Use a ratchet wrench.



15

Remove the fastening bolts.



16

Remove the caliper bracket.



17

Remove the brake disc.



18

Clean the hub. Use a wire brush. Use all-purpose cleaning spray.







Treat the contacting surface. Use ceramic grease.



20

Install the brake disc.



21

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake discs Toyota RAV4 II. After applying the spray, wait a few minutes.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.



22

Install the brake caliper bracket.



23

Install the fastening bolts.



24

Screw in the fasteners of the brake caliper bracket. Use a drive socket #17. Use a ratchet wrench.



25

Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use antisqueal paste.

Replacement: brake discs – Toyota RAV4 II. AUTODOC experts recommend:

• Make sure the disc surface is clean before installing the pads.





Install the brake pads.



27

Treat the brake caliper pistons. Use a nylon cleaning brush. Use a brake cleaner.



AUTODOC recommends:

• After applying the spray, wait a few minutes.

28

Wind back the brake caliper pistons. Use brake caliper wind back tool.



29

Install the brake caliper and fix it.





Install the fastening bolts.



31

Tighten the brake caliper fasteners. Use a combination spanner #17. Use a drive socket #14. Use a torque wrench. Tighten it to 26 Nm torque.



32 Tighten the brake caliper bracket fasteners. Use a drive socket #17. Use a torque wrench. Tighten it to 106 nm torque.



33

Treat the surface where the brake disc contacts the wheel rim. Use ceramic grease.







Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

• Replacement: brake discs – Toyota RAV4 II. After applying the spray, wait a few minutes.

35

Install the wheel.



AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Toyota RAV4 II

36

Screw in the wheel bolts. Use wheel impact socket #19.





Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 103 Nm torque.



38

Remove the jacks and chocks.



Replacement: brake discs – Toyota RAV4 II. AUTODOC recommends:

- Without starting the engine, press the brake pedal several times until you feel significant resistance.
- Check the brake fluid level in the expansion tank and refill if necessary.





Tighten the brake fluid reservoir cap. Close the hood.






VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

BRAKE DISCS: A WIDE SELECTION



CHOOSE CAR PARTS FOR TOYOTA RAV4 II

BRAKE DISCS FOR TOYOTA: BUY NOW

BRAKE DISCS FOR TOYOTA RAV4 II: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.