



How to change spark
plugs on **RENAULT CLIO**
II Box (SB0/1/2_) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

RENAULT CLIO II Box (SB0/1/2_) 1.1, RENAULT CLIO II Box (SB0/1/2_) 1.2

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: RENAULT TWINGO I (C06_) 1.2

REPLACEMENT: SPARK PLUGS – RENAULT CLIO II BOX (SB0/1/2_). TOOLS YOU NEED:



- High-temperature anti-seize lubricant
- Spark plug socket # 16
- Round-nose pliers
- Torque wrench
- Fender cover

Buy tools

Replacement: spark plugs – RENAULT CLIO II Box (SB0/1/2_). Professionals recommend:


- The replacement procedure is the same for all spark plugs.
- Warning! Shut down the engine before starting any work – RENAULT CLIO II Box (SB0/1/2_)

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Remove the engine cover.




4 Remove the spark plug wire connectors from the spark plug wells. Use round-nose pliers.




Replacement: spark plugs – RENAULT CLIO II Box (SB0/1/2_). Tip from AUTODOC:

- Be careful to avoid damaging spark plug wires.
- Remember the sequence of the spark plug wires connectors.


5 Clean dirt, dust and debris from inside the spark plug wells.



6 Unscrew the spark plugs. Use the spark plug socket #16.



7 Take out the spark plugs. Use the spark plug socket #16.




8 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.



9 Install the new spark plugs into their mounting seats. Use the spark plug socket #16.


10 Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 25 nm torque.



Replacement: spark plugs – RENAULT CLIO II Box (SB0/1/2_). AUTODOC experts recommend:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

11 Treat the spark plug wire connectors. Use high-temperature grease.



12

Install the spark plug wire connectors into the spark plug wells. Use round-nose pliers. Make sure you hear a click indicating that it is locked in place.




Replacement: spark plugs – RENAULT CLIO II Box (SB0/1/2_). Tip:

- Follow the installation sequence.

13

Install the engine cover.



14

Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

15

Shut off the engine.

16

Remove the fender protection cover.

17

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SPARK PLUGS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.