



How to change fuel filter  
on **RENAULT LAGUNA**  
**Coupe (DT0/1)** –  
replacement guide

## SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

### **i Important!**


This replacement procedure can be used for:

RENAULT LAGUNA Coupe (DT0/1) 2.0 16V Turbo, RENAULT LAGUNA Coupe (DT0/1) 3.5 V6, RENAULT LAGUNA Coupe (DT0/1) 2.0 GT, RENAULT LAGUNA Coupe (DT0/1) 3.5 V6 (DT0P, DT0C)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: RENAULT MEGANE II Saloon (LM0/1\_) 1.4

## REPLACEMENT: FUEL FILTER – RENAULT LAGUNA COUPE (DT0/1). LIST OF THE TOOLS YOU'LL NEED:



- Fuel line pliers
- Fluid container
- Crow bar

[Buy tools](#)

Replacement: fuel filter – RENAULT LAGUNA Coupe (DT0/1). Tip from AUTODOC experts:

- Ensure adequate ventilation of the workplace. Fuel vapors are poisonous.
- Please note: all work on the car – RENAULT LAGUNA Coupe (DT0/1) – should be done with the engine switched off.

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the fuel door. Unscrew the fuel filler cap.




2

Lift the car and set it on jack stands.


3

Prepare a container for fluids.



4

Squeeze the clips and detach the fuel supply lines from the fuel filter housing. Use fuel line pliers.



Replacement: fuel filter – RENAULT LAGUNA Coupe (DT0/1). Tip from AUTODOC experts:

- Be careful! Fuel may leak from the filter housing and hoses.

5

Remove the fuel filter. Use a crowbar. Put the old filter cartridge in the container.



6

Install a new fuel filter.



Replacement: fuel filter – RENAULT LAGUNA Coupe (DT0/1). Professionals recommend:

- Remember, it is important not to mix up the input and output of the filter. Arrows on the filter indicate the direction of fuel flow.
- During installation, take care to prevent dust and dirt from getting into the fuel filter housing.
- Attention! Use quality filters – RENAULT LAGUNA Coupe (DT0/1).

7

Connect the fuel lines to the fuel filter and lock the fastening clips.



8

Lower the car.

9

Tighten the fuel filler cap. Close the fuel door.



Replacement: fuel filter – RENAULT LAGUNA Coupe (DT0/1). AUTODOC experts recommend:

- Before starting off, switch the ignition on and off several times. This should be done to activate the fuel pump to make it pump fuel through the fuel system.

10

Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

11

Shut off the engine.

Replacement: fuel filter – RENAULT LAGUNA Coupe (DT0/1). Tip:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

**WELL DONE!** 

[VIEW MORE TUTORIALS](#)

## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**





 GET IT ON  
Google Play

 Download on the  
App Store

Download

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**FUEL FILTER: A WIDE SELECTION**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.