



How to change tailgate  
struts on **Renault Scenic**  
**2** – replacement guide

## VIDEO TUTORIAL



### **i Important!**

This replacement procedure can be used for:

RENAULT Scénic II (JM) 1.9 dCi, RENAULT Scénic II (JM) 2.0, RENAULT Scénic II (JM) 1.5 dCi, RENAULT Scénic II (JM) 1.6, RENAULT Scénic II (JM) 1.4, RENAULT Grand Scénic II (JM) 1.6, RENAULT Grand Scénic II (JM) 2.0, RENAULT Grand Scénic II (JM) 1.5 dCi, RENAULT Grand Scénic II (JM) 1.9 dCi, RENAULT Scénic II (JM) 2.0 16V Turbo, RENAULT Scénic II (JM) 2.0 dCi, RENAULT Scénic II (JM) 1.6 16V, RENAULT Grand Scénic II (JM) 2.0 dCi, RENAULT Scénic II (JM) 1.9 D, RENAULT Scénic II (JM) 1.6 BiFuel, (+ 1)

The steps may slightly vary depending on the car design.

REPLACEMENT: TAILGATE STRUTS – RENAULT SCENIC  
2. LIST OF THE TOOLS YOU'LL NEED:



- Phillips screwdriver
- Flat Screwdriver
- Hydraulic transmission jack

**BUY TOOLS**

Replacement: tailgate struts – Renault Scenic 2. AUTODOC recommends:


- Right and left gas struts of the boot lid should be replaced simultaneously.
- The replacement procedure is identical for the right and left gas struts of the boot lid.
- All work should be done with the engine stopped.

**REPLACEMENT: TAILGATE STRUTS – RENAULT SCENIC 2.  
RECOMMENDED SEQUENCE OF STEPS:**


**1** Open the boot lid.




**2** Unscrew the fastener of the rear light cluster. Use a Phillips screwdriver.



**3** Take out the rear light cluster.



4 Disconnect the rear light bulbs connector. Use a flat screwdriver.



5 Support the boot lid. Use a hydraulic transmission jack.



6 Release the circlip connecting the gas strut to the car body. Use a flat screwdriver.



7 Release the circlip connecting the gas strut to the boot lid. Use a flat screwdriver.




**Replacement: tailgate struts – Renault Scenic 2. Professionals recommend:**

- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.


8

Remove the boot lid gas strut.



9

Install the new boot lid gas strut.




Replacement: tailgate struts – Renault Scenic 2. AUTODOC experts recommend:

- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.

10

Snap on the circlip connecting the gas strut to the boot lid.




11


Snap on the circlip connecting the gas strut to the car body. Use a flat screwdriver.



12 Attach the rear light bulbs connectors.



13 Install the rear light cluster.



14 Screw in the fasteners of the rear light cluster. Use a Phillips screwdriver.



15 Remove the hydraulic transmission jack.



**AUTODOC recommends:**

- Replacement: tailgate struts – Renault Scenic 2. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.


16

Check the working condition of the boot lid gas springs after they are installed.



17

Close the lid of the luggage compartment.



**WELL DONE!** 

**VIEW MORE TUTORIALS**



## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING

**AUTODOC+**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR RENAULT**

**TAILGATE STRUTS: A WIDE SELECTION**

**CHOOSE CAR PARTS FOR RENAULT SCENIC 2**

**TAILGATE STRUTS FOR RENAULT: BUY NOW**

**TAILGATE STRUTS FOR RENAULT SCENIC 2: THE BEST  
DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.