# **+** AUTODOC CLUB

How to change front anti roll bar links on **SEAT Ibiza IV Hatchback (6J5, 6P1)** – replacement guide







#### SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

## i Important!

This replacement procedure can be used for:

SEAT Ibiza IV Hatchback (6J5, 6P1) 1.2, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.6 LPG, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.4, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.4 TDI, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.9 TDI, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.6, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.4 TSI, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.6 TDI, SEAT Ibiza IV Hatchback (6J5, 6P1) 2.0 TDI, SEAT Ibiza IV Hatchback (6J5, 6P1) 1.2 TDI

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: SEAT Ibiza III Hatchback (6L) 1.4 16V

CLUB.AUTODOC.CO.UK 1–9







## REPLACEMENT: ANTI ROLL BAR LINKS – SEAT IBIZA IV HATCHBACK (6J5, 6P1). TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Combination spanner #17

- XZN socket bit # 6
- Drive socket # 17
- Wheel impact socket #17
- Ratchet wrench
- Wheel chock

**Buy tools** 

CLUB.AUTODOC.CO.UK 2–9







## Replacement: anti roll bar links – SEAT Ibiza IV Hatchback (6J5, 6P1). Tip from AUTODOC:

- Replace the stabiliser links on SEAT Ibiza IV Hatchback (6J5, 6P1) in pairs.
- The replacement procedure is identical for both stabiliser links on the same axle.
- Warning! Shut down the engine before starting any work SEAT Ibiza IV Hatchback (6J5, 6P1)

### CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



Loosen the wheel mounting bolts. Use wheel impact socket #17.



Raise the front of the car and secure on supports.

CLUB.AUTODOC.CO.UK 3-9







4

Unscrew the wheel bolts.



## Replacement: anti roll bar links – SEAT Ibiza IV Hatchback (6J5, 6P1). Tip:

• To avoid injury, hold up the wheel when unscrewing the bolts.

5

Remove the wheel.



6

Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.



CLUB.AUTODOC.CO.UK 4–9







Unscrew the fastener connecting the stabilizer link to the shock strut. Use a drive socket #17. Use a ratchet wrench.



Unscrew the fasteners connecting the stabiliser link to the stabiliser bar. Use a combination spanner #17. Use XZN #6. Use a ratchet wrench.



g Remove the stabilizer rod.



Replacement: anti roll bar links – SEAT Ibiza IV Hatchback (6J5, 6P1). Tip from AUTODOC:

• Examine stabiliser bushes. Replace them if needed.

CLUB.AUTODOC.CO.UK 5–9







Clean the mounting seats of the stabiliser link. Use a wire brush. Use WD-40 spray.




11 Install the transverse stabilizer link.



Tighten the fastener connecting the stabilizer link to the shock strut. Use a combination spanner #17. Use a drive socket #17. Use a torque wrench. Tighten it to 40 Nm torque.



Tighten the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #17. Use a drive socket #17. Use a torque wrench. Tighten it to 40 Nm torque.



CLUB.AUTODOC.CO.UK 6-9







Treat all joints of the stabiliser link. Use copper grease.



Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



Clean the brake disk surface. Use a brake cleaner.



## **AUTODOC** recommends:

 Replacement: anti roll bar links – SEAT Ibiza IV Hatchback (6J5, 6P1). After applying the spray, wait a few minutes.

17 Install the wheel.



CLUB.AUTODOC.CO.UK 7–9







## Replacement: anti roll bar links – SEAT Ibiza IV Hatchback (6J5, 6P1). Professionals recommend:

• To avoid injury, hold up the wheel when screwing in the fastening bolts.

18 Sci

Screw in the wheel bolts. Use wheel impact socket #17.



Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 nm torque.



Remove the jacks and chocks.






**VIEW MORE TUTORIALS** 

CLUB.AUTODOC.CO.UK 8-9





# AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

**ANTI ROLL BAR LINKS: A WIDE SELECTION** 

### **① DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.

CLUB.AUTODOC.CO.UK 9-9