



How to change pollen  
filter on **SEAT Toledo III**  
**(5P2)** – replacement  
guide

### SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

#### **Important!**

This replacement procedure can be used for:

SEAT Toledo III (5P2) 1.6, SEAT Toledo III (5P2) 2.0 FSI, SEAT Toledo III (5P2) 1.9 TDI, SEAT Toledo III (5P2) 2.0 TDI 16V, SEAT Toledo III (5P2) 1.8 TFSI, SEAT Toledo III (5P2) 2.0 TDI, SEAT Toledo III (5P2) 2.0 TFSI, SEAT Toledo III (5P2) 1.4 16V, SEAT Toledo III (5P2) 1.4 TSI

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: AUDI A3 Sportback (8PA) 1.2 TSI

Replacement: pollen filter – SEAT Toledo III (5P2). AUTODOC experts recommend:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- Replacement: pollen filter – SEAT Toledo III (5P2). Take the following steps:

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

**1** Move the passenger seat fully backwards.



**2** Unscrew the fasteners of the bottom trim panel.



**3** Bend the bottom trim upwards.



**4** Remove the cabin filter housing cover.



**AUTODOC recommends:**

- Replacement: pollen filter – SEAT Toledo III (5P2). Do not use excessive force when removing the part as this may damage it.

**5** Remove the cabin filter.



**Replacement: pollen filter – SEAT Toledo III (5P2). Tip from AUTODOC experts:**

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

**6** Install the cabin filter to its mounting seat.



**AUTODOC recommends:**

- Replacement: pollen filter – SEAT Toledo III (5P2). Be sure to position the filtering element correctly. Avoid misalignment.
- Follow the air flow direction arrow on the filter.
- Attention! Use quality filters – SEAT Toledo III (5P2).

**7** Reinstall the cabin filter housing cover. Make sure you hear a click indicating that it is locked in place.



**AUTODOC recommends:**

- Replacement: pollen filter – SEAT Toledo III (5P2). Do not use excessive force during installation. This may damage the fasteners.

**8** Install the glove box bottom cover.



**9** Screw in the fasteners of the bottom trim panel.



**10** Return the passenger seat to its initial position.



**11** Switch on the ignition.

**12** Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.

**13** Switch off the ignition.

**WELL DONE!** 

**VIEW MORE TUTORIALS**

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
 **Google Play**

 **Download on the App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**POLLEN FILTER: A WIDE SELECTION**

## **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.