



How to change rear anti
roll bar bushes on **VW**
Sharan 1 – replacement
guide

VIDEO TUTORIAL




i Important!

This replacement procedure can be used for:

VW SHARAN (7M8, 7M9, 7M6) 1.9 TDI, VW SHARAN (7M8, 7M9, 7M6) 2.0, VW SHARAN (7M8, 7M9, 7M6) 2.8 VR6, VW SHARAN (7M8, 7M9, 7M6) 2.8 VR6 Syncro, VW SHARAN (7M8, 7M9, 7M6) 1.8 T 20V, VW SHARAN (7M8, 7M9, 7M6) 2.0 TDI, VW SHARAN (7M8, 7M9, 7M6) 2.8 V6 24V, VW SHARAN (7M8, 7M9, 7M6) 2.8 V6 24V 4motion, VW SHARAN (7M8, 7M9, 7M6) 1.9 TDI 4motion, VW SHARAN (7M8, 7M9, 7M6) 2.0 LPG

The steps may slightly vary depending on the car design.

REPLACEMENT: ANTI ROLL BAR BUSHES – VW SHARAN 1. TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Drive socket # 13
- Ratchet wrench
- Torque wrench
- Flat Screwdriver
- Water pump pliers
- Hydraulic transmission jack

[BUY TOOLS](#)

Replacement: anti roll bar bushes – VW Sharan 1. Tip from AUTODOC:

- Both stabilizer bushes should be replaced simultaneously.
- The replacement procedure is identical for the right and left stabilizer bushes.
- All work should be done with the engine stopped.

REPLACEMENT: ANTI ROLL BAR BUSHES – VW SHARAN 1. RECOMMENDED SEQUENCE OF STEPS:

1

Lift the car using a jack or place it over an inspection pit.




2


Clean the fasteners of the stabilizer bush brackets. Use a wire brush. Use WD-40 spray.



- 3 Unscrew the fasteners of the stabilizer bush brackets. Use a drive socket #13. Use a ratchet wrench.




- 4 Remove the stabilizer bush brackets. Use a flat screwdriver.



- 5 Secure the rear axle beam. Use a hydraulic transmission jack.



- 6 Remove the stabilizer bushes. Use a flat screwdriver. Use water pump pliers.



- 7 Clean the mounting seats of the stabilizer bushes. Use a wire brush. Use WD-40 spray.

- 8 Install the new stabilizer bushes. Use a flat screwdriver.




- 9 Remove the mounting from under the rear axle beam.


AUTODOC recommends:

- Replacement: anti roll bar bushes – VW Sharan 1. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

- 10 Install the stabilizer bush brackets.



- 11 Screw the fasteners of the stabilizer bush brackets. Use a drive socket #13. Use a torque wrench. Tighten it to 35 nm torque.



- 12 Treat the fasteners of the stabilizer bush brackets. Use copper grease.

13

Lower the car.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VW

ANTI ROLL BAR BUSHES: A WIDE SELECTION

CHOOSE CAR PARTS FOR VW SHARAN 1

ANTI ROLL BAR BUSHES FOR VW: BUY NOW

**ANTI ROLL BAR BUSHES FOR VW SHARAN 1: THE BEST
DEALS & OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.