



How to change air filter  
on **VW Sharan 1** –  
replacement guide

## VIDEO TUTORIAL

** Important!**


This replacement procedure can be used for:

VW SHARAN (7M8, 7M9, 7M6) 1.9 TDI, VW SHARAN (7M8, 7M9, 7M6) 2.0, VW SHARAN (7M8, 7M9, 7M6) 1.8 T 20V, VW SHARAN (7M8, 7M9, 7M6) 2.8 V6 24V, VW SHARAN (7M8, 7M9, 7M6) 2.8 V6 24V 4motion, VW SHARAN (7M8, 7M9, 7M6) 1.9 TDI 4motion, VW SHARAN (7M8, 7M9, 7M6) 2.0 TDI, VW SHARAN (7M8, 7M9, 7M6) 2.0 LPG

---

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – VW SHARAN 1. LIST OF THE TOOLS YOU'LL NEED:



- Clic-R collar pliers
- Phillips screwdriver
- Microfibre towel
- Fender cover

**BUY TOOLS**

Replacement: air filter – VW Sharan 1. Tip from AUTODOC:


- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car – VW Sharan 1 – should be done with the engine switched off.

**CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:**


**1** Open the hood.




**2** Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



**3** Undo the fastening screws of the air filter cover. Use a Phillips screwdriver.



**4** Loosen the fastening clamp connecting the air duct to the air filter housing. Use clic-R collar pliers.



**5** Detach the air duct housing from the air filter housing.



**6** Cover the air intake hose with a microfibre towel to prevent dust and dirt from getting into the system.




**7** Take off the filter lid.




**AUTODOC recommends:**

- Replacement: air filter – VW Sharan 1. Do not use excessive force when removing the part as this may damage it.


**8** Remove the filter element from the filter housing.



**9** Clean the air filter cover and housing.



**10** Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.




**AUTODOC recommends:**

- Replacement: air filter – VW Sharan 1. Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.

11

Reinstall the air filter cover. Fasten it.




**AUTODOC recommends:**

- Replacement: air filter – VW Sharan 1. Do not use excessive force during installation. This may damage the part.

12

Remove the microfibre towel from the air intake hose.




13

Connect the air intake pipe to the air filter housing.




14

Secure the air intake hose with a clamp. Use a Phillips screwdriver.




**15** Screw in the fastening screws of the air filter cover. Use a Phillips screwdriver.




**16** Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

**17** Shut off the engine.

**18** Remove the fender protection cover.



**19** Close the hood.



**WELL DONE!** 

**VIEW MORE TUTORIALS**



# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR VW**

**AIR FILTER: A WIDE SELECTION**

**CHOOSE CAR PARTS FOR VW SHARAN 1**

**AIR FILTER FOR VW: BUY NOW**

**AIR FILTER FOR VW SHARAN 1: THE BEST DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.