



How to change rear coil
springs on **SKODA Fabia**
I Saloon (6Y3) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

SKODA Fabia I Saloon (6Y3) 1.9 TDI, SKODA Fabia I Saloon (6Y3) 1.4 16V, SKODA Fabia I Saloon (6Y3) 1.4, SKODA Fabia I Saloon (6Y3) 2.0, SKODA Fabia I Saloon (6Y3) 1.2, SKODA Fabia I Saloon (6Y3) 1.4 TDI

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: SKODA Fabia I Combi (6Y5) 1.2

REPLACEMENT: COIL SPRINGS – SKODA FABIA I
SALOON (6Y3). TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Combination spanner #16
- Drive socket # 16
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Hydraulic transmission jack
- Wheel chock

[Buy tools](#)

Replacement: coil springs – SKODA Fabia I Saloon (6Y3). Tip from AUTODOC:

- Both coil springs of the rear suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right coil springs of the rear suspension.
- Please note: all work on the car – SKODA Fabia I Saloon (6Y3) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #17.



3

Raise the rear of the car and secure on supports.

4

Unscrew the wheel bolts.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
SKODA Fabia I Saloon (6Y3)


5

Remove the wheel.



6

Secure the rear axle beam. Use a hydraulic transmission jack.



7

Clean the shock absorber fasteners. Use a wire brush. Use WD-40 spray.



- 8 Unscrew the lower fastener of the shock absorber. Use a drive socket #16. Use a combination spanner #16. Use a ratchet wrench.




- 9 Lower the hydraulic transmission jack by 10-15 cm.



AUTODOC recommends:

- Replacement: coil springs – SKODA Fabia I Saloon (6Y3). Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

- 10 Remove the spring.



11 Clean the coil spring mounting seats. Use a wire brush.




12 Install the spring.



13 Secure the rear axle beam. Use a hydraulic transmission jack.



14 Tighten the lower fastener of the shock absorber. Use a drive socket #16. Use a combination spanner #16. Use a torque wrench. Tighten it to 40 Nm torque. +90°



AUTODOC recommends:

- Important! Be sure to use new fasteners.

15 Remove the mounting from under the rear axle beam.



AUTODOC recommends:

- SKODA Fabia I Saloon (6Y3) – Do not lower the transmission jack sharply to avoid damaging components and mechanisms of the car.

16 Clean the wheel rim mounting seat. Use a wire brush. Treat the contacting surface. Use copper grease.



17 Install the wheel.



AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. SKODA Fabia I Saloon (6Y3)

18

Screw in the wheel bolts. Use wheel impact socket #17.




19

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 120 nm torque.



20

Remove the jacks and chocks.



WELL DONE! 👍

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING

AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

COIL SPRINGS: A WIDE SELECTION

(i) DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.