



How to change front anti
roll bar links on **SKODA**
Scala Hatchback –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!


This replacement procedure can be used for:

SKODA Scala Hatchback 1.0 TSI, SKODA Scala Hatchback 1.5 TSI, SKODA Scala Hatchback 1.6 TDI, SKODA Scala Hatchback 1.0 TGI CNG, SKODA Scala Hatchback 1.6 SRE

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: SKODA Fabia I Combi (6Y5) 1.2

REPLACEMENT: ANTI ROLL BAR LINKS – SKODA SCALA HATCHBACK. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Combination spanner #16
- Combination spanner #17
- HEX bit No.H5
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench

Buy tools

AUTODOC recommends:


- Replace the stabiliser links on SKODA Scala Hatchback in pairs.
- The replacement procedure is identical for both stabiliser links on the same axle.
- Please note: all work on the car – SKODA Scala Hatchback – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Secure the wheels with chocks.



2 Loosen the wheel mounting bolts. Use wheel impact socket #17.



3 Raise the front of the car and secure on supports.

4

Unscrew the wheel bolts.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
SKODA Scala Hatchback

5

Remove the wheel.



6.1

Clean the stabiliser link fasteners.



6.2

Use a wire brush. Use WD-40 spray.



- 7 Unscrew the nut and remove the stabilizer rod from the shock strut. Use HEX No.H5. Use a combination spanner #16. Use a ratchet wrench.



- 8 Unscrew the fasteners connecting the stabiliser link to the stabiliser bar. Use HEX No.H5. Use a combination spanner #16. Use a ratchet wrench.




- 9 Remove the stabilizer rod.




- 10 Install a new rod, tighten the fasteners.



- 11** Tighten the fastener connecting the stabilizer link to the shock strut. Use HEX No.H5. Use a combination spanner #17. Use a torque wrench. Tighten it to 40 Nm torque.



- 12** Tighten the fastener connecting the stabilizer link to the stabilizer bar. Use HEX No.H5. Use a combination spanner #17. Use a torque wrench. Tighten it to 40 Nm torque.



- 13** Clean the wheel rim mounting seat. Use a wire brush. Treat the contacting surface. Use copper grease.



- 14** Install the wheel.



AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. SKODA Scala Hatchback

15


Screw in the wheel bolts. Use wheel impact socket #17.

**16**

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 Nm torque.

**17**

Remove the jacks and chocks.

**WELL DONE!** **VIEW MORE TUTORIALS**

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

Download on the
 **App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

ANTI ROLL BAR LINKS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.