



How to change front
strut mount on **TOYOTA**
Yaris Verso (_P2_) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


Important!

This replacement procedure can be used for:
TOYOTA Yaris Verso (_P2_) 1.3, TOYOTA Yaris Verso (_P2_) 1.5, TOYOTA Yaris Verso (_P2_) 1.4 D-4D

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: TOYOTA Yaris Hatchback (_P1_) 1.3 (NCP10_, SCP12_)

REPLACEMENT: STRUT MOUNT – TOYOTA YARIS
 VERSO (_P2_). TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Combination spanner #12
- Combination spanner #19
- Drive socket # 14
- Drive socket # 17
- Drive socket # 19
- Wheel impact socket #21
- Ratchet wrench
- Torque wrench
- Flat Screwdriver
- Hydraulic strut spring compressor
- Fender cover
- Wheel chock

Buy tools

Replacement: strut mount – TOYOTA Yaris Verso (_P2_). AUTODOC recommends:

- All mounts of the front shock struts should be replaced simultaneously.
- The replacement procedure is identical for the mounts of the left and right shock struts of the front suspension.
- Be sure to replace all self-locking nuts and bolts during installation.
- Please note: all work on the car – TOYOTA Yaris Verso (_P2_) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Secure the wheels with chocks.

2 Loosen the wheel mounting bolts. Use wheel impact socket #21.



3 Raise the front of the car and secure on supports.

4 Unscrew the wheel bolts.



Replacement: strut mount – TOYOTA Yaris Verso (_P2_). Tip:


- To avoid injury, hold up the wheel when unscrewing the bolts.

5 Remove the wheel.




6 Clean the fastener of the bracket that connects the brake hose to the shock strut. Use a wire brush. Use WD-40 spray.

7 Unscrew the brake hose fastening bracket from the shock strut. Use a drive socket #14. Use a ratchet wrench.




8 Remove the bracket from the shock absorber strut.



9 Clean the fasteners connecting the shock strut to the steering knuckle. Use a wire brush. Use WD-40 spray.

10

Unscrew the lower fastener connecting the shock strut to the steering knuckle. Use a combination spanner #19. Use a drive socket #19. Use a ratchet wrench.



11

Remove the fastening bolts. Disconnect the steering knuckle from the shock absorber strut.

12

Lower the car. Open the bonnet.

13


Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

14

Clean the fasteners of the shock strut upper mount. Use a wire brush. Use WD-40 spray.

15

Unscrew the top fastening of the shock strut mount. Use a combination spanner #12.




Replacement: strut mount – TOYOTA Yaris Verso (_P2_). AUTODOC recommends:

- To avoid injuries, hold the shock strut when undoing the fastening bolts.

16

Remove the suspension strut.



17

Set the shock absorber strut on the spring compressor tool.



Replacement: strut mount – TOYOTA Yaris Verso (_P2_). Tip from AUTODOC experts:


- Note that when using a spring compressor, spring coils need to be securely gripped, compressing the spring on the opposite sides.
- Ensure the correct position of the spring in the retainer.
- Make sure that the spring coils tightly entered the lock handles.

18

Compress the spring.

19


Remove the protective cap from the shock absorber strut mount. Use a flat screwdriver.



20 Treat the shock strut rod. Use a wire brush. Use WD-40 spray.



21 Remove the strut piston rod nut. Use a drive socket #17. Use a ratchet wrench.



22 Remove the top strut mount. Use a flat screwdriver.



23 Clean the mounting seat of the shock strut mount. Use a wire brush. Use WD-40 spray.

Replacement: strut mount – TOYOTA Yaris Verso (_P2_). Professionals recommend:

- Examine the shock absorber dust cap and the bump stop. Replace them if necessary.

24 Install a new strut mount.




25 Tighten the shock strut piston rod nut. Use a drive socket #17. Use a torque wrench. Tighten it to 33 Nm torque.



Replacement: strut mount – TOYOTA Yaris Verso (_P2_). AUTODOC experts recommend:

- Check to make sure the spring is positioned correctly. Avoid its misalignment.

26 Treat the shock strut rod. Use copper grease.



27 Install the protective cap onto the shock absorber strut mount.



28 Decompress the spring.

29 Remove the assembled shock strut.




30 Clean the mounting seats of the shock strut. Use a wire brush. Use WD-40 spray.



31 Install the shock strut into the wheel arch.


32 Screw the top fastening of the shock strut mount.



AUTODOC recommends:

- Important! Hold the suspension strut while screwing in the fastening bolts.
TOYOTA Yaris Verso (_P2_)

33 Tighten the upper fastener of the shock absorber strut mount. Use a combination spanner #12. Use a torque wrench. Tighten it to 35 Nm torque.



34 Treat the fasteners of the shock strut mount. Use copper grease.

35 Remove the fender protection cover. Close the hood.


36 Raise the front of the car and secure on supports.



37 Fix the shock absorber strut on the steering knuckle.


38 Install the fastening bolts.

39 Tighten the lower fasteners connecting the shock strut to the steering knuckle. Use a combination spanner #19. Use a drive socket #19. Use a torque wrench. Tighten it to 132 Nm torque.




40 Treat the shock strut fasteners. Use copper grease.


41 Install the bracket onto the shock absorber strut.



42 Tighten the brake hose fastening bracket to the shock strut. Use a drive socket #14. Use a ratchet wrench.



43 Treat the surface where the brake disc contacts the wheel rim. Use copper grease.




44 Clean the brake disk surface. Use a brake cleaner.



Replacement: strut mount – TOYOTA Yaris Verso (_P2_). Tip from AUTODOC experts:

- After applying the spray, wait a few minutes.

45 Install the wheel.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. TOYOTA Yaris Verso (_P2_)

46 Screw in the wheel bolts. Use wheel impact socket #21.



47 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #21. Use a torque wrench. Tighten it to 103 Nm torque.



48

Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

STRUT MOUNT: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.