



How to change air filter
on **Volvo V70 SW** –
replacement guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:

VOLVO V60 (155, 157) 2.0 T, VOLVO V60 (155, 157) 2.0 D3 / D4, VOLVO V60 (155, 157) 2.4 D5, VOLVO V60 (155, 157) 2.4 D5 AWD, VOLVO V60 (155, 157) 1.6 T3, VOLVO V60 (155, 157) 1.6 T4, VOLVO V60 (155, 157) 2.0 T5, VOLVO V70 III (135) 1.6 T4, VOLVO XC60 (156) 2.0 T5, VOLVO S80 II (124) 1.6 T4, VOLVO S80 II (124) 2.0 T5, VOLVO S80 II (124) 2.0 D3 / D4, VOLVO V70 III (135) 2.0 T5, VOLVO S60 II (134) 1.6 DRIVE / D2, VOLVO V70 III (135) 2.0 D3 / D4, (+ 94)

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – VOLVO V70 SW. TOOLS
YOU'LL NEED:



- Impact socket №7
- Ratchet wrench
- Microfibre towel
- Fender cover


BUY TOOLS

Replacement: air filter – Volvo V70 SW. Professionals recommend:


- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car – Volvo V70 SW – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet.



2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3 Unplug the mass air flow sensor connector.




4

Detach the air intake hose clamp. Use a drive socket #7. Use a ratchet wrench.




5

Release the air filter cover clips.



6

Slightly raise the cover of the air filter housing.




7

Remove the filter element from the filter housing.



8

Cover the air intake hose with a microfibre towel to prevent dust and dirt from getting into the system.



9

Clean the air filter cover and housing.



Replacement: air filter – Volvo V70 SW. Tip from AUTODOC:

- Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.
- Remove the microfibre towel from the air intake hose.

10

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.




AUTODOC recommends:

- Replacement: air filter – Volvo V70 SW. Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.

11

Reinstall the air filter cover. Fasten it.



12

Press the air filter cover clips into place.



13

Plug in the mass air flow sensor connector.



14

Fasten the clamp on the air intake hose. Use a drive socket #7. Use a ratchet wrench.

**15**

Remove the fender protection cover.

**16**

Close the hood.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VOLVO

AIR FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR VOLVO V70 SW

AIR FILTER FOR VOLVO: BUY NOW

**AIR FILTER FOR VOLVO V70 SW: THE BEST DEALS &
OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.