



How to change front
suspension strut on
**VAUXHALL Corsa Mk I
(B) Hatchback (S93)** –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.0 i 12V, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.2 i, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.4 i, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.4 i S, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.4 i 16V, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.6 i 16V, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.6 GSI 16V, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.5 D, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.5 TD, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.7 D, VAUXHALL Corsa Mk I (B) Hatchback (S93) 1.2 i 16V

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: OPEL Corsa B Hatchback (S93) 1.4 i (F08, F68, M68)

**REPLACEMENT: SUSPENSION STRUT – VAUXHALL
CORSA MK I (B) HATCHBACK (S93). TOOLS YOU MIGHT
NEED:**



- Wire brush
- WD-40 spray
- Brake cleaner
- Ceramic grease
- Copper grease
- Torque wrench
- Combination spanner #18
- Drive socket # 6
- Drive socket # 13
- Drive socket # 18
- Drive socket # 19
- HEX bit no.H5.
- HEX bit no.H6.
- Wheel impact socket #17
- Ratchet wrench
- Hydraulic strut spring compressor
- Hydraulic transmission jack
- Fender cover
- Wheel chock


Buy tools

Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
AUTODOC experts recommend:

- Both shock struts of the front suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right shock struts of the front suspension.
- All work should be done with the engine stopped.

REPLACEMENT: SUSPENSION STRUT – VAUXHALL CORSA MK I (B) HATCHBACK (S93). RECOMMENDED SEQUENCE OF STEPS:

- 1 Open the bonnet.
- 2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.
- 3 Clean the shock strut fasteners. Use a wire brush. Use WD-40 spray.
- 4 Loosen the upper fasteners of the suspension strut. Use a drive socket #13. Use a ratchet wrench.



Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
Tip:

- Do not completely unscrew the upper fasteners as they may hold also other suspension components.

5 Secure the wheels with chocks.



6 Loosen the wheel mounting bolts. Use wheel impact socket #17.




7 Raise the car.

Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
AUTODOC experts recommend:

- If you are using a jack, make sure it rests on a flat surface without any unevenness.
- Be sure to additionally secure the car with jack stands.

8 Unscrew the wheel bolts.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
VAUXHALL Corsa Mk I (B) Hatchback (S93)

9

Remove the wheel.




10

Unscrew the ABS sensor wiring bracket. Use a drive socket #6. Use a ratchet wrench.




11

Disconnect the ABS sensor wiring.



12


Clean the fasteners connecting the shock strut to the steering knuckle. Use a wire brush. Use WD-40 spray.




13 Prop up the steering knuckle. Use a hydraulic transmission jack.



14 Unscrew the fasteners connecting the suspension strut to the steering knuckle. Use a combination spanner #18. Use a drive socket #18. Use a ratchet wrench.



15 Remove the fastening bolts.



16 Disconnect the steering knuckle from the shock absorber strut.

17 Unscrew the upper fasteners of the shock strut.




AUTODOC recommends:

- VAUXHALL Corsa Mk I (B) Hatchback (S93) – To avoid injury, hold the suspension strut while unscrewing the fastening bolts.


18

Remove the suspension strut.



19

Set the suspension strut on the spring compressor tool.



**Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
Tip from AUTODOC experts:**

- Note that when using a spring compressor, spring coils need to be securely gripped, compressing the spring on the opposite sides.
- Ensure the correct position of the spring in the retainer.
- Make sure that the spring coils tightly entered the lock handles.

20 Compress the spring.



21 Treat the shock strut rod. Use a wire brush. Use WD-40 spray.



22 Remove the strut piston rod nut. Use HEX No.H6. Use a drive socket #19.



23 Remove the top strut mount.




Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).

Tip:

- Thoroughly examine the shock absorber mount, dust boot, bump stop. Replace them if necessary.


24

Release the coil spring.




25

Remove the shock absorber dust cap and the bump stop.




26

Remove the spring.



27

Remove the old shock absorber from the hydraulic coil spring compressor.



Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
AUTODOC recommends:

- Before installing a new shock absorber you should pump it manually 3-5 times.


28

Install the new shock absorber on the hydraulic coil spring compressor.




29

Install the spring on the shock absorber.




30

Install the dust sleeve and the bump stop on the new shock absorber.




31

Compress the spring.



32 Install the upper strut mount and the strut mount bearing.



33 Tighten the shock strut piston rod nut. Use HEX No.H5. Use a drive socket #19. Use a torque wrench. Tighten it to 55 nm torque.




AUTODOC recommends:

- Check to make sure the spring is positioned correctly. Avoid its misalignment.

34 Treat the shock strut rod. Use copper grease.



35 Decompress the spring.




36 Remove the assembled shock strut.



37 Clean the mounting seats of the shock strut.



38 Install the shock strut into the wheel arch.



39 Secure the upper fasteners of the shock strut. Do not tighten it.



AUTODOC recommends:


- VAUXHALL Corsa Mk I (B) Hatchback (S93) – To avoid injury, hold the suspension strut while screwing in the fastening bolts.

40 Fix the shock absorber strut on the steering knuckle.


41 Install the fastening bolts.




42 Tighten the lower suspension strut fasteners. Use a combination spanner #18. Use a drive socket #18. Use a ratchet wrench.



43 Tighten the lower fasteners connecting the shock strut to the steering knuckle. Use a combination spanner #18. Use a drive socket #18. Use a torque wrench. Tighten it to 90 Nm torque.+45°+15°



44 Connect the ABS sensor wiring.



45

Tighten the ABS sensor wiring bracket. Use a drive socket #6. Use a ratchet wrench.



46

Remove the support from under the steering knuckle.



AUTODOC recommends:

- Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93). Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.


47

Treat the surface where the brake disc contacts the wheel rim. Use ceramic grease.



48

Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: suspension strut – VAUXHALL Corsa Mk I (B) Hatchback (S93).
After applying the spray, wait a few minutes.

49

Install the wheel.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. VAUXHALL Corsa Mk I (B) Hatchback (S93)

50

Screw in the wheel bolts. Use wheel impact socket #17.



- 51 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 110 Nm torque.



- 52 Remove the jacks and chocks.



- 53 Tighten the upper fasteners of the shock strut. Use a drive socket #13. Use a torque wrench. Tighten it to 30 Nm torque.



- 54 Treat the fasteners of the shock strut mount. Use copper grease.



- 55 Remove the fender protection cover.

56

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SHOCK ABSORBERS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.