




How to change front  
windshield wipers on  
**Mercedes Vito W639** –  
replacement guide

## VIDEO TUTORIAL



### **ⓘ Important!**

This replacement procedure can be used for:

MERCEDES-BENZ S-Class Saloon (W140) S 350 Turbo-D (140.134), MERCEDES-BENZ S-Class Saloon (W140) S 280 (140.028), MERCEDES-BENZ S-Class Saloon (W140) 300 SE 2.8 (140.028), MERCEDES-BENZ S-Class Saloon (W140) 300 SE/SEL/S320 3.2 (140.032, 140.033), MERCEDES-BENZ S-Class Saloon (W140) S 420 (140.042), MERCEDES-BENZ S-Class Saloon (W140) 400 SE/SEL/S420 4.2 (140.042, 140.043), MERCEDES-BENZ S-Class Saloon (W140) S 500 (140.050, 140.051), MERCEDES-BENZ S-Class Saloon (W140) 500 SE/SEL 5.0 (140.050, 140.051), MERCEDES-BENZ S-Class Saloon (W140) S 600 (140.056, 140.057), MERCEDES-BENZ S-Class Saloon (W140) 600 SE/SEL 6.0 (140.056, 140.057), MERCEDES-BENZ S-Class Coupe (C140) SEC/CL 500 (140.070), MERCEDES-BENZ S-Class Coupe (C140) SEC/CL 600 (140.076), MERCEDES-BENZ S-Class Coupe (C140) SEC/CL 420 (140.063), MERCEDES-BENZ SPRINTER 3,5-t Bus (906) 318 CDI 3.0 (906.731, 906.733, 906.735), MERCEDES-BENZ SPRINTER 3,5-t Bus (906) 319 CDI / BlueTEC 3.0 (906.731, 906.733, 906.735), (+ 334)

The steps may slightly vary depending on the car design.

## Replacement: windshield wipers – Mercedes Vito W639. Tip from AUTODOC experts:

- Always replace front wiper blades together. It will ensure efficient and uniform cleaning of the windshield.
- Don't confuse the wiper blades of the driver and passenger side.
- The replacement procedure for both wiper blades is identical.
- Please note: all work on the car – Mercedes Vito W639 – should be done with the engine switched off.

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1

Prepare the new windscreen wiper blades.




2


Pull the wiper arm away from the glass surface until it stops.



**3** Press the clip.




**4** Remove the blade from the wiper arm.



**Replacement: windshield wipers – Mercedes Vito W639. Tip from AUTODOC:**

- When replacing the wiper blade, take caution to prevent the spring-loaded wiper arm from hitting the glass.

**5** Install the new wiper blade and carefully press the wiper arm down to the glass.



## Replacement: windshield wipers – Mercedes Vito W639. AUTODOC recommends:

- Don't touch the wiper blade at the working rubber edge to prevent damage to the graphite coating.
- Ensure that the blade rubber strip fits tightly to the glass along the entire length.

6

Switch on the ignition.



7

After installation check the wipers performance. The blades shouldn't intersect or bump against the windshield seal.

**WELL DONE!** 

**VIEW MORE TUTORIALS**

## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
 **Google Play**

 **Download on the App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR MERCEDES**

**WINDSHIELD WIPERS: A WIDE SELECTION**

**CHOOSE CAR PARTS FOR MERCEDES VITO W639**

**WINDSCREEN WIPERS FOR MERCEDES: BUY NOW**

**WINDSCREEN WIPERS FOR MERCEDES VITO W639: THE  
BEST DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.