



How to change fuel filter
on **VOLVO S60 II (134)** –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

i Important!

This replacement procedure can be used for:

VOLVO S60 II (134) 1.6 T4F, VOLVO S60 II (134) 1.6 T3, VOLVO S60 II (134) 1.6 T4, VOLVO S60 II (134) 2.5 T5, VOLVO S60 II (134) 3.0 T6 AWD, VOLVO S60 II (134) 2.0 T6, VOLVO S60 II (134) 2.0 T5, VOLVO S60 II (134) 2.0 T, VOLVO S60 II (134) 3.0 T AWD, VOLVO S60 II (134) 2.0 T5 AWD, VOLVO S60 II (134) 2.5 T5 AWD, VOLVO S60 II (134) 1.5 T3, VOLVO S60 II (134) 2.0 T3, VOLVO S60 II (134) 2.0 T4, VOLVO S60 II (134) 2.0 T6 AWD, (+ 5)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VOLVO V70 III (135) 2.0 FlexiFuel

REPLACEMENT: FUEL FILTER – VOLVO S60 II (134).
 TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- All-purpose cleaning spray
- Torx bit T30
- Ratchet wrench
- Flat screwdriver
- Fluid container

Buy tools


Replacement: fuel filter – VOLVO S60 II (134). Tip from AUTODOC experts:

- Ensure adequate ventilation of the workplace. Fuel vapors are poisonous.
- Please note: all work on the car – VOLVO S60 II (134) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the fuel door.



2

Unscrew the fuel filler cap.




3


Lift the car using a jack or place it over an inspection pit.

4

Prepare a container for fluids.



5 Clean the fuel filter mounting bracket. Use a wire brush. Use WD-40 spray.




6 Loosen the fuel filter fasteners. Use Torx T30. Use a ratchet wrench.



7 Clean the fasteners of the fuel supply lines. Use all-purpose cleaning spray.



8 Disconnect the fuel supply lines from the fuel filter. Use a flat screwdriver.



Replacement: fuel filter – VOLVO S60 II (134). AUTODOC recommends:

- Be careful! Fuel may leak from the filter housing and hoses.

9

Remove the fuel filter.



10

Clean the fuel lines. Use all-purpose cleaning spray.



11


Install a new fuel filter.




AUTODOC recommends:

- During installation, take care to prevent dust and dirt from getting into the fuel filter housing.

12 Connect the fuel lines to the fuel filter.



13 Screw in the fuel filter mounting bracket. Use Torx T30. Use a ratchet wrench.



14 Take the fluid container away from under the fuel filter.




15 Lower the car.

16 Tighten the fuel filler cap.



17

Close the fuel door.



Replacement: fuel filter – VOLVO S60 II (134). Tip:

- Before starting off, switch the ignition on and off several times. This should be done to activate the fuel pump to make it pump fuel through the fuel system.

18

Run the engine for a few minutes.

AUTODOC recommends:

- This is necessary in order to make sure that the component operates properly.

19

Shut off the engine.

Replacement: fuel filter – VOLVO S60 II (134). Professionals recommend:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

FUEL FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.