



How to change
windscreen wiper arm on
VW Golf V Variant (1K5)
– replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

VW Golf V Variant (1K5) 1.6, VW Golf V Variant (1K5) 1.4 TSI, VW Golf V Variant (1K5) 1.9 TDI, VW Golf V Variant (1K5) 2.0 TDI 16V, VW Golf V Variant (1K5) 2.0 TDI, VW Golf V Variant (1K5) 1.4, VW Golf V Variant (1K5) 2.0, VW Golf V Variant (1K5) 1.9 TDI 4motion

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VW Golf V Hatchback (1K1) 1.6

REPLACEMENT: WINDSCREEN WIPER ARM – VW GOLF V VARIANT (1K5). TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Torque wrench
- Drive socket # 13
- Ratchet wrench
- Flat Screwdriver
- Universal puller
- Fender cover

Buy tools

Replacement: windscreen wiper arm – VW Golf V Variant (1K5). AUTODOC experts recommend:


- Replace the wiper arms in pairs.
- Don't mix up the wiper arms on the driver's and passenger's side.
- The replacement procedure is the same for both wiper arms.
- Please note: all work on the car – VW Golf V Variant (1K5) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Remove the windscreen wiper arm nut covers. Use a flat screwdriver.



4 Clean the fasteners of the wiper arms. Use a wire brush. Use WD-30 spray.




5

Unscrew the fasteners of the windscreen wiper arms. Use a drive socket #13. Use a ratchet wrench.



6

Remove the wiper arms. Use a universal puller.



7

Remove the wiper blades.




8

Clean the pivots of the windscreen wiper arms. Use a wire brush. Use WD-40 spray.

9


Treat the pivots of the windscreen wiper arms. Use copper grease.



10 Attach the wiper blades to the new arms.



11 Reinstall the wiper arms.



Replacement: windscreen wiper arm – VW Golf V Variant (1K5). Tip from AUTODOC experts:

- Make sure not to mix up the wiper arms on the driver's and passenger's sides.

12 Tighten the wiper arm fasteners. Use a drive socket #13. Use a torque wrench. Tighten it to 16 Nm torque.



13 Treat the wiper arm fasteners. Use copper grease.



14 Install the nut covers of the windscreen wiper arms.




15 Remove the cap of the rear wiper arm fastener.



16 Clean the rear wiper arm fastener. Use a wire brush. Use WD-40 spray.



17 Unscrew the rear wiper arm fastener. Use a drive socket #13. Use a ratchet wrench.



18 Remove the wiper arm. Use a universal puller.



19 Clean the rear wiper arm mounting seat. Use a wire brush. Use WD-40 spray.

20 Treat the mounting seat of the rear wiper arm. Use copper grease.




21 Install a new wiper arm.




22 Screw in the rear wiper arm fastener. Use a drive socket #13. Use a torque wrench. Tighten it to 16 Nm torque.



23 Treat the rear wiper arm fastener. Use copper grease.



24 Install the cap of the rear wiper arm fastener.



25 Remove the fender protection cover.

26 Close the hood.

27 Switch on the ignition.

28 After installation check the wipers performance. The blades shouldn't intersect or bump against the windshield seal.



29 Switch off the ignition.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

WINDSCREEN WIPER ARM: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.