



How to change spark
plugs on **VW Multivan VI**
(SGF, SGM, SGN) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

VW Multivan VI (SGF, SGM, SGN) 2.0 TSI, VW Multivan VI (SGF, SGM, SGN) 2.0 TSI 4motion

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VW GOLF VI (5K1) 2.0 GTi

REPLACEMENT: SPARK PLUGS – VW MULTIVAN VI
(SGF, SGM, SGN). TOOLS YOU'LL NEED:



- High-temperature anti-seize lubricant
- Electronic spray
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- Crow bar
- Fender cover

Buy tools

Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). Professionals recommend:


- The replacement procedure is the same for all spark plugs.
- All work should be done with the engine stopped.

REPLACEMENT: SPARK PLUGS – VW MULTIVAN VI (SGF, SGM, SGN). TAKE THE FOLLOWING STEPS:


1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Remove the engine cover.



4 Unplug the connectors from the ignition coils.



5 Raise a little the wiring of the ignition coils and move it aside.



6 Pry up the ignition coil (4 pieces). Use a crowbar.



7 Take out the ignition coils from the spark plug wells.



Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). Tip:

- Remember the sequence of steps for ignition coil demounting.

8 Clean dirt, dust and debris from inside the spark plug wells.



9 Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.



10 Take out the spark plugs.



11 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs. Treat the surface of the terminals of the new spark plugs. Use high-temperature grease.




12

Install the new spark plugs into their mounting seats.



13

Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 25 nm torque.




Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). AUTODOC recommends:

- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.
- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.

14

Install the ignition coils to the spark plug wells. Make sure you hear a click indicating that it is locked in place.




Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). Tip from AUTODOC experts:

- Follow the installation sequence.

15

Treat the ignition coil connector with electronic spray. The spray will protect the electrical contacts from corrosion, oxidation, and will reduce the contact resistance.




AUTODOC recommends:

- Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). After applying the spray, wait a few minutes.


16

Plug in the connectors of the ignition coils.



17

Secure the wiring of the ignition coils in its mounting seats.




Replacement: spark plugs – VW Multivan VI (SGF, SGM, SGN). AUTODOC experts recommend:

- Make sure that all connectors are attached to the ignition coils.

18

Install the engine cover and secure it. Make sure you hear a click indicating that it is locked in place.



19

Remove the fender protection cover.

20

Close the hood.

21

Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

22

Shut off the engine.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SPARK PLUGS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.