



How to change fuel filter
on **VW PASSAT Saloon**
(32B) diesel –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

VW PASSAT Saloon (32B) 1.6 TD, VW PASSAT Saloon (32B) 1.6 D

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VW GOLF III (1H1) 1.9 D

REPLACEMENT: FUEL FILTER – VW PASSAT SALOON
(32B). TOOLS YOU NEED:



- All-purpose cleaning spray
- Drive socket # 7
- Drive socket # 13
- Ratchet wrench
- Round-nose pliers
- Hand-operated fluid syringe
- Fender cover

Buy tools

Replacement: fuel filter – VW PASSAT Saloon (32B). AUTODOC recommends:

- Ensure adequate ventilation of the workplace. Fuel vapors are poisonous.
- All work should be done with the engine stopped.

REPLACEMENT: FUEL FILTER – VW PASSAT SALOON (32B). RECOMMENDED SEQUENCE OF STEPS:


1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.


3 Clean the fasteners of the fuel supply lines. Use all-purpose cleaning spray.



4 Loosen the fuel filter mounting. Use a drive socket #13. Use a ratchet wrench.



5 Loosen the fuel supply lines fastening to the fuel filter. Use a drive socket #7. Use a ratchet wrench.



6 Disconnect the fuel supply lines from the fuel filter. Use round-nose pliers.



Replacement: fuel filter – VW PASSAT Saloon (32B). Tip:

- Be careful! Fuel may leak from the filter housing and hoses.

7 Remove the fuel line retaining clip. Use round-nose pliers.



8 Remove the fuel line.



9 Remove the fuel filter.



10 Install a new fuel filter.



AUTODOC recommends:

- VW PASSAT Saloon (32B) – It's important to only use high-quality filters.

11 Clean the fuel lines. Use all-purpose cleaning spray.



12 Install the fuel line.



13 Install the fuel line retaining clip.



14 Install the fuel line.




15 Screw the fastener attaching the fuel supply line to the fuel filter housing. Use a drive socket #7. Use a ratchet wrench.




16 Fill the new filter with fuel. Use a hand-operated fluid syringe.




17 Install the fuel line.



18 Screw the fastener attaching the fuel supply line to the fuel filter housing. Use a drive socket #7. Use a ratchet wrench.



19 Screw in the fuel filter mounting bracket. Use a drive socket #13. Use a ratchet wrench.



20 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

21 Shut off the engine.

22 Remove the fender protection cover.

23 Close the hood.

Replacement: fuel filter – VW PASSAT Saloon (32B). Tip from AUTODOC experts:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

FUEL FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.