



How to change glass for
wing mirror on **VW Polo
Saloon (9A4, 9A2, 9N2,
9A6)** – replacement
guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!


This replacement procedure can be used for:

VW Polo Saloon (9A4, 9A2, 9N2, 9A6) 1.4, VW Polo Saloon (9A4, 9A2, 9N2, 9A6) 1.9 SDI, VW Polo Saloon (9A4, 9A2, 9N2, 9A6) 1.4 TDI

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: SKODA Octavia II Combi (1Z5) 1.8 TSI

REPLACEMENT: GLASS FOR WING MIRROR – VW POLO SALOON (9A4, 9A2, 9N2, 9A6). TOOLS YOU NEED:



• Electronic spray

• Plastic trim tool

Buy tools

Replacement: glass for wing mirror – VW Polo Saloon (9A4, 9A2, 9N2, 9A6).
AUTODOC recommends:


- The replacement procedure is identical for the right and left side mirror glass.
- All work should be done with the engine stopped.

REPLACEMENT: GLASS FOR WING MIRROR – VW POLO SALOON (9A4, 9A2, 9N2, 9A6). RECOMMENDED SEQUENCE OF STEPS:


1 Tilt the mirror glass out of the housing.



2 Carefully release the mirror glass from its attachment. Use a plastic trim tool.



3 Remove the mirror glass.




AUTODOC recommends:

- Replacement: glass for wing mirror – VW Polo Saloon (9A4, 9A2, 9N2, 9A6). To avoid damaging the part during installation, do not use excessive force.


4

Detach the mirror heating connectors.




5

Treat the mirror heating connectors. Use dielectric grease.




6

Attach the mirror heating connectors.



7

Install the new mirror glass. Make sure you hear a click indicating that it is locked in place.



Replacement: glass for wing mirror – VW Polo Saloon (9A4, 9A2, 9N2, 9A6).
Professionals recommend:

- Do not apply excessive force when installing the part. Otherwise you may damage the fasteners.
- Make sure the mirror glass is positioned correctly. It should be aligned with the locking tabs on the housing.


8

Clean the mirror glass.



9

Switch on the ignition. This is necessary in order to make sure that the component operates properly.



10

Switch off the ignition.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

GLASS FOR WING MIRROR: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.