



How to change rear
brake discs on **VW**
Transporter VI Minibus
(SGB, SGG, SGJ) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

 Important!

This replacement procedure can be used for:

VW Transporter VI Minibus (SGB, SGG, SGJ) 2.0 TDI, VW Transporter VI Minibus (SGB, SGG, SGJ) 2.0 TDI 4motion, VW Transporter VI Minibus (SGB, SGG, SGJ) 2.0 TSI, VW Transporter VI Minibus (SGB, SGG, SGJ) 2.0 TSI 4motion, VW Transporter VI Minibus (SGB, SGG, SGJ) ABT e-Caravelle

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VW Multivan V (7HM, 7HN, 7HF, 7EF, 7EM, 7EN) 1.9 TDI

**REPLACEMENT: BRAKE DISCS – VW TRANSPORTER VI
MINIBUS (SGB, SGG, SGJ). TOOLS YOU MIGHT NEED:**



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- Brake caliper guide pins grease
- Sealant
- Ceramic grease
- Copper grease
- Torque wrench
- Drive socket # 12
- Drive socket # 21
- Torx bit M10
- Wheel impact socket #19
- Ratchet wrench
- Tap wrench
- Brake caliper wind back tool
- Crow bar
- Wheel chock

Buy tools

Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ).
 AUTODOC experts recommend:

- Replace the brake disks on the car VW Transporter VI Minibus (SGB, SGG, SGJ) in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- Please note: all work on the car – VW Transporter VI Minibus (SGB, SGG, SGJ) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet. Unscrew the brake fluid reservoir cap.

2 Secure the wheels with chocks.



3 Loosen the wheel mounting bolts. Use wheel impact socket #19.



4 Raise the rear of the car and secure on supports.

5 Unscrew the wheel bolts.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts. VW Transporter VI Minibus (SGB, SGG, SGJ)

6 Remove the wheel.



7 Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



8


Unscrew the brake caliper fasteners. Use a drive socket #12. Use a ratchet wrench.

**9**

Spread the brake pads. Use a crowbar.

**10**

Remove the brake caliper. Use a crowbar.



Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ). Tip from AUTODOC experts:


- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

11

Detach the connector of the brake pad wear sensor. Use a crowbar.


12

Remove the brake pads. Use a crowbar.




13

Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.




14 Unscrew the brake caliper bracket fasteners. Use a drive socket #21. Use a ratchet wrench. Use a tap wrench.




15 Remove the fastening bolts (2 pieces).

16 Remove the caliper bracket.




17 Clean the brake disc fastener. Use a wire brush. Use WD-40 spray.

18 Unscrew the brake disc fastening. Use Torx M10. Use a ratchet wrench.



19 Remove the brake disc.



20

Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.




21

Install the brake disc.




22

Tighten the brake disc fastening. Use Torx M10. Use a torque wrench. Tighten it to 15 Nm torque.



23

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ). After applying the spray, wait a few minutes.

24 Remove the guide pins from the brake caliper.

25 Clean the brake caliper guide pins.



26 Treat the brake caliper guide pins. Use the brake caliper guide pin grease.




27 Screw in the guide pins.

28 Treat the brake caliper bracket fasteners. Use a sealant.




29 Install the brake caliper bracket.




30 Install the fastening bolts (2 pieces).

31 Tighten the brake caliper bracket. Use a drive socket #21. Use a torque wrench. Tighten it to 165 Nm torque.



32 Install the brake pads.



33 Attach the connector of the brake pad wear sensor.


34 Treat the brake caliper piston. Use a nylon cleaning brush. Use a brake cleaner.



Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ). Tip from AUTODOC experts:

- After applying the spray, wait a few minutes.


35 Press in the brake caliper piston. Use brake caliper wind back tool.



36.1 Install the brake caliper and fix it.



36.2 Use a drive socket #12. Use a torque wrench. Tighten it to 30 nm torque.



37 Treat the surface where the brake disc contacts the wheel rim. Use ceramic grease.



38

Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ). After applying the spray, wait a few minutes.

39

Install the wheel.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. VW Transporter VI Minibus (SGB, SGG, SGJ)

40

Screw in the wheel bolts. Use wheel impact socket #19.




41

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 180 Nm torque.



42

Remove the jacks and chocks.



**Replacement: brake discs – VW Transporter VI Minibus (SGB, SGG, SGJ).
AUTODOC recommends:**

- Check the brake fluid level in the expansion tank and refill if necessary.
- Without starting the engine, press the brake pedal several times until you feel significant resistance.

43

Tighten the brake fluid reservoir cap. Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BRAKE DISCS: A WIDE SELECTION

(i) DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.