




How to change air filter
on **VW Transporter VI**
Platform / Chassis (SFD,
SFE, SFL, SFZ) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ) 2.0 TDI, VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ) 2.0 TDI 4motion, VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ) 2.0 TSI

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: VW Transporter V Van (7HA, 7HH, 7EA, 7EH) 1.9 TDI

REPLACEMENT: AIR FILTER – VW TRANSPORTER VI PLATFORM / CHASSIS (SFD, SFE, SFL, SFZ). TOOLS YOU'LL NEED:



- Electronic spray
- Clic-R collar pliers
- Microfibre towel
- Fender cover

[Buy tools](#)

Replacement: air filter – VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ). AUTODOC experts recommend:


- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- All work should be done with the engine stopped.

REPLACEMENT: AIR FILTER – VW TRANSPORTER VI PLATFORM / CHASSIS (SFD, SFE, SFL, SFZ). TAKE THE FOLLOWING STEPS:


1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.


3 Unplug the mass air flow sensor connector.




4 Detach the air intake hose clamp. Use clic-R collar pliers.




5 Disconnect the air intake pipe from the air filter housing.



6 Cover the air intake hose with a microfibre towel to prevent dust and dirt from getting into the system.




7 Release the air filter cover clips.



8 Take off the filter lid.



9 Remove the filter element from the filter housing.



10

Clean the air filter cover and housing.




Replacement: air filter – VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ). Tip from AUTODOC experts:

- Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.

11


Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.




AUTODOC recommends:

- Replacement: air filter – VW Transporter VI Platform / Chassis (SFD, SFE, SFL, SFZ). Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.


- 12** Reinstall the air filter cover. Fasten it.



- 13** Press the air filter cover clips into place.



- 14** Remove the microfibre towel from the air intake hose.



- 15** Connect the air intake pipe to the air filter housing.




- 16** Fasten the clamp on the air intake hose. Use clic-R collar pliers.




17

Treat the mass air flow sensor connector. Use dielectric grease.



18

Plug in the mass air flow sensor connector.



19

Remove the fender protection cover.

20

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING





 GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

AIR FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.