



How to change tailgate
struts on **Toyota Yaris P1**
– replacement guide

VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:

TOYOTA Yaris Hatchback (_P1_) 1.0 (SCP10_), TOYOTA Yaris Hatchback (_P1_) 1.5 (NCP13_), TOYOTA Yaris Hatchback (_P1_) 1.4 D-4D (NLP10_), TOYOTA Yaris Hatchback (_P1_) 1.3 (SCP12_)

The steps may slightly vary depending on the car design.

REPLACEMENT: TAILGATE STRUTS – TOYOTA YARIS
P1. TOOLS YOU'LL NEED:



- Nylon cleaning brush
- WD-40 spray
- Torque wrench
- Drive socket # 10
- Ratchet wrench
- Hydraulic transmission jack

BUY TOOLS

Replacement: tailgate struts – Toyota Yaris P1. AUTODOC recommends:

- Right and left gas struts of the boot lid should be replaced simultaneously.
- The replacement procedure is identical for the right and left gas struts of the boot lid.
- Please note: all work on the car – Toyota Yaris P1 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1 Open the boot lid.



2 Support the boot lid. Use a hydraulic transmission jack.



3 Unscrew the fastener connecting the boot lid gas strut to the body. Use a drive socket #10. Use a ratchet wrench.




4 Unscrew the fastener connecting the gas strut to the boot lid. Use a drive socket #10. Use a ratchet wrench.



Replacement: tailgate struts – Toyota Yaris P1. Tip:

- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.

5 Remove the boot lid gas strut.




6

Clean the mounting seats of the boot strut. Use a nylon cleaning brush. Use WD-40 spray.



7

Install the new boot lid gas strut.




Replacement: tailgate struts – Toyota Yaris P1. Tip from AUTODOC experts:


- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.

8

Tighten the fastener connecting the gas strut to the boot lid. Use a drive socket #10. Use a torque wrench. Tighten it to 13 Nm torque.



- 9** Tighten the fastener connecting the boot lid gas strut to the body. Use a drive socket #10. Use a torque wrench. Tighten it to 13 Nm torque.



- 10** Remove the hydraulic transmission jack.



AUTODOC recommends:

- Replacement: tailgate struts – Toyota Yaris P1. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

- 11** Check the working condition of the boot lid gas springs after they are installed.



12

Close the lid of the luggage compartment.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

TAILGATE STRUTS: A WIDE SELECTION

CHOOSE CAR PARTS FOR TOYOTA YARIS P1

TAILGATE STRUTS FOR TOYOTA: BUY NOW

**TAILGATE STRUTS FOR TOYOTA YARIS P1: THE BEST DEALS
& OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.