



How to change air filter
on **Toyota Yaris Mk2** –
replacement guide

VIDEO TUTORIAL


** Important!**

This replacement procedure can be used for:

TOYOTA Yaris Hatchback (_P13_) 1.0 (KSP130_), TOYOTA Yaris Hatchback (_P1_) 1.0 (SCP10_), TOYOTA Yaris Hatchback (_P1_) 1.3 (SCP12_), TOYOTA AYGO (WNB1_, KGB1_) 1, TOYOTA Yaris Hatchback (_P9_) 1.0 VVT-i (KSP90_), TOYOTA Yaris Hatchback (_P9_) 1.3 VVT-i (SCP90_), TOYOTA DYNA 100 Platform/Chassis (YH_) 1.8 (YH81_), TOYOTA AYGO (WNB1_, KGB1_) 1.0 GPL (KGB10_), TOYOTA Yaris Hatchback (_P9_) 1.0 GPL (KSP90_), TOYOTA Dyna 150 Platform / Chassis (_Y_) 2.0 (YY61_), TOYOTA Yaris Hatchback (_P9_) 1.0 VVT-i (KSP90)

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – TOYOTA YARIS MK2.
LIST OF THE TOOLS YOU'LL NEED:



• Microfibre towel

• Fender cover


BUY TOOLS

Replacement: air filter – Toyota Yaris Mk2. Tip from AUTODOC:


- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car – Toyota Yaris Mk2 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1 Open the bonnet.



2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.




3 Release the air filter cover clips.



4 Take off the filter lid.




5 Cover the air intake hose with a microfibre towel to prevent dust and dirt from getting into the system.



6 Remove the filter element from the air filter cover.



7 Clean the air filter cover and housing.



8 Remove the microfibre towel from the air intake hose.

9

Install a new filter element into the air filter cover. Make sure that the filter edge fits tight to the housing.




Replacement: air filter – Toyota Yaris Mk2. Tip from AUTODOC experts:

- Check out the correct location of the filter element. Do not skew.
- Attention! Use quality filters – Toyota Yaris Mk2.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.


10

Reinstall the air filter cover. Fasten it.



11

Press the air filter cover clips into place.



12

Remove the fender protection cover.



13

Close the hood.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

AIR FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR TOYOTA YARIS MK2

AIR FILTER FOR TOYOTA: BUY NOW

AIR FILTER FOR TOYOTA YARIS MK2: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.