How to change pollen filter on **Opel Zafira B A05** – replacement guide



VIDEO TUTORIAL




(i) Important!

This replacement procedure can be used for:

OPEL Astra G CC (T98) 1.2 16V (F08, F48), OPEL Astra G CC (T98) 1.6 (F08, F48), OPEL Astra G CC (T98) 1.6 16V (F08, F48), OPEL Astra G CC (T98) 1.8 16V (F08, F48), OPEL Astra G CC (T98) 2.0 16V (F08, F48), OPEL Astra G CC (T98) 1.7 TD (F08, F48), OPEL Astra G CC (T98) 2.0 DI (F08, F48), OPEL Astra G Caravan (T98) 1.2 16V (F35), OPEL Astra G Caravan (T98) 1.6 (F35), OPEL Astra G Caravan (T98) 1.6 16V (F35), OPEL Astra G Caravan (T98) 1.8 16V (F35), OPEL Astra G Caravan (T98) 2.0 16V (F35), OPEL Astra G Caravan (T98) 1.7 TD (F35), OPEL Astra G Caravan (T98) 2.0 DI (F35), OPEL Astra G Caravan (T98) 2.2 DTI (F35), (+ 87)

The steps may slightly vary depending on the car design.



O




Replacement: pollen filter – Opel Zafira B A05. Tip from AUTODOC experts:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

REPLACEMENT: POLLEN FILTER – OPEL ZAFIRA B A05. TAKE THE FOLLOWING STEPS:



Move the passenger seat fully backwards.



2

Spread a cloth under the cabin filter cover to protect the interior upholstery from getting dirty.



Unscrew the fasteners of the passenger side kick panel. Use a flat screwdriver.





4

Unscrew the glove box fastening screws. Use Torx T20.



5

Open the glove box.



6

Unscrew the glove box fastening screws. Use Torx T20.



7

Remove the glovebox.



Replacement: pollen filter – Opel Zafira B A05. Tip:

• Be careful to avoid damaging the glove compartment fasteners.



8

Unplug the glove box light connector.



9

Remove the fasteners of the air duct housing.



10

Detach the air duct housing from the air filter housing.



11

Unscrew the fasteners of the cabin filter housing cover. Use Torx T20.



12

Remove the cabin filter housing cover.





AUTODOC recommends:

• Replacement: pollen filter – Opel Zafira B A05. Do not use excessive force when removing the part as this may damage it.

Remove the cabin filter.



Replacement: pollen filter – Opel Zafira B A05. Tip from AUTODOC:

• Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

14

13

Install the cabin filter to its mounting seat.





Replacement: pollen filter - Opel Zafira B A05. AUTODOC experts recommend:

- Follow the air flow direction arrow on the filter.
- Replacement: pollen filter Opel Zafira B A05. Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.



Reinstall the cabin filter housing cover.



16

Screw in the fasteners of the cabin filter housing cover. Use Torx T20.





Install the air duct housing.





18

Install the air duct housing fasteners.



19

Plug in the glove box light connector.



20

Install the glove box.



21

Screw the glove box fastening screws. Use Torx T20.



22

Close the glove box.







Screw the glove box fastening screws. Use Torx T20.



24

Screw in the fasteners of the passenger side kick panel. Use a flat screwdriver.

25 Remove the cloth.



Return the passenger seat to its initial position.



27

Switch on the ignition.



28 Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.







Switch off the ignition.






VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR OPEL

POLLEN FILTER: A WIDE SELECTION



CHOOSE CAR PARTS FOR OPEL ZAFIRA B A05

POLLEN FILTER FOR OPEL: BUY NOW

POLLEN FILTER FOR OPEL ZAFIRA B A05: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.