How to change front brake pads on Peugeot 206 CC 2D – replacement guide

VIDEO TUTORIAL

ⓘ Important!

This replacement procedure can be used for:
PEUGEOT 1007 (KM_) 1.6 16V, PEUGEOT 206 CC (2D) 1.6, PEUGEOT 206 CC (2D) 1.6 16V, PEUGEOT 206 Hatchback (2A/C) 1.6, PEUGEOT 206 Hatchback (2A/C) 1.6 16V, PEUGEOT 206 Saloon 1.6 16V, PEUGEOT 206 SW (2E/K) 1.6, PEUGEOT 206 SW (2E/K) 1.6 16V, PEUGEOT 206 SW (2E/K) 1.6 LPG, PEUGEOT 307 (3A/C) 1.6, PEUGEOT 307 (3A/C) 1.6 16V, PEUGEOT 307 (3A/C) 1.6 BioFlex, PEUGEOT PARTNER Box (5_, G_) 1.6, PEUGEOT PARTNER Combispace (5_, G_) 1.6 16V, PEUGEOT PARTNER Combispace (5_, G_) 1.6 Flexfuel

---

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE PADS – PEUGEOT 206 CC 2D. TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Anti-squeal paste
- Copper grease
- Drive socket # 13
- Wheel impact socket #19
- Brake caliper wind back tool
- Ratchet wrench
- Torque wrench
- Crow bar
- Wheel chock

Replacement: brake pads – Peugeot 206 CC 2D. AUTODOC recommends:

- Perform the replacement of brake pads in complete set for each axis. This provides effective braking.
- The replacement procedure is identical for all brake pads on the same axle.
- All work should be done with the engine stopped.

REPLACEMENT: BRAKE PADS – PEUGEOT 206 CC 2D. RECOMMENDED SEQUENCE OF STEPS:

1

Open the bonnet. Unscrew the brake fluid reservoir cap.

2

Secure the wheels with chocks.

3

Loosen the wheel mounting bolts. Use wheel impact socket #19.

4

Raise the front of the car and secure on supports.

5

Unscrew the wheel bolts.

Replacement: brake pads – Peugeot 206 CC 2D. Tip:

- To avoid injury, hold up the wheel when unscrewing the bolts.

6

Remove the wheel.

7

Spread the brake pads. Use a crowbar.

8

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.

9

Unscrew the brake caliper fastening. Use a drive socket #13. Use a ratchet wrench.

10



Remove the brake caliper.

Replacement: brake pads – Peugeot 206 CC 2D. AUTODOC experts recommend:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

11



Remove the brake pads.

Replacement: brake pads – Peugeot 206 CC 2D. Professionals recommend:

- Measure the brake disc thickness. Upon reaching the wear limit the part must be replaced.

12

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.

AUTODOC recommends:

- Replacement: brake pads – Peugeot 206 CC 2D. After applying the spray, wait a few minutes.

13

Treat the brake caliper piston. Use a brake cleaner.

Replacement: brake pads – Peugeot 206 CC 2D. Tip from AUTODOC:

- After applying the spray, wait a few minutes.

14

Press in the brake caliper piston. Use brake caliper wind back tool.

15

Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use anti-squeal paste.

Replacement: brake pads – Peugeot 206 CC 2D. AUTODOC experts recommend:

- Make sure the disc surface is clean before installing the pads.

16

Install new brake pads.

Replacement: brake pads – Peugeot 206 CC 2D. Tip from AUTODOC experts:

- Make sure the pads are installed with linings facing the disc.

17

Install the brake caliper and fix it. Use a drive socket #13. Use a torque wrench. Tighten it to 35 Nm torque.

18



Clean the brake disk surface. Use a brake cleaner.

AUTODOC recommends:

- Replacement: brake pads – Peugeot 206 CC 2D. After applying the spray, wait a few minutes.

19



Treat the surface where the brake disc contacts the wheel rim. Use copper grease.

20

Install the wheel.

Replacement: brake pads – Peugeot 206 CC 2D. AUTODOC recommends:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

21

Screw in the wheel bolts. Use wheel impact socket #19.

22

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 120 Nm torque.

23

Remove the jacks and chocks.

AUTODOC recommends:

- Important! Replacement: brake pads – Peugeot 206 CC 2D. Check the brake fluid level in the reservoir and top up if necessary.

24

Tighten the brake fluid reservoir cap.

AUTODOC recommends:

- Peugeot 206 CC 2D – Press the brake pedal several times with the engine shut down until you feel the resistance built up.

25

Close the hood.

Replacement: brake pads – Peugeot 206 CC 2D. AUTODOC experts recommend:

- Slow down smoothly for first 150-200 km after the brake pads replacement. Avoid unneccessary and sharp braking to a stop.

DID YOU FIND THESE INSTRUCTIONS HELPFUL?

YES NO

BECOME A MEMBER OF AUTODOC CLUB!

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR



BUY SPARE PARTS FOR PEUGEOT

BRAKE PADS: A WIDE SELECTION

CHOOSE CAR PARTS FOR PEUGEOT 206 CC 2D

BRAKE PADS FOR PEUGEOT: BUY NOW

BRAKE PADS FOR PEUGEOT 206 CC 2D: THE BEST DEALS & OFFERS

ⓘ Disclaimer:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AutoDoc shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AutoDoc shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AutoDoc shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AutoDoc strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2018 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by Autodoc GmbH.